GastroCH4ECK® Gastrolyzer® **INSTALLATION & CAUTIONS**

Installation

On receipt of a new GastroCH4ECK®:

- 1. Remove the unit from the packaging supplied to you
- 2. Place the unit in the location it is most likely to be used and ensure a clearance of 30cm (1ft) above and 15cm (6in) at the sides and rear of the GastroCH4ECK®
- 3. **DO NOT** switch on for the first 24 hours
- 4. After 24 hours, switch the device on and allow ≤2 minutes for the GastroCH₄ECK® to start up
- 5. Please allow the GastroCH₄ECK® to be switched on for at least 5 minutes prior to calibration.

Cautions

- Do not use this device outside the operational temperatures of between 15-35°C. If the device has been exposed to temperatures outside of the 15-35°C range, then please leave in an area within the range for a minimum of 6 hours.
- Do not use alcohol based hand cleaners before using this device. If the device has been exposed to alcohol based hand cleaners, then please leave for 6 hours for the device sensors to settle before using or calibrating the device.
- The GastroCH₄ECK[®] should be switched off once every 24 hours.



USA Sales Service and Support

C=Vita www.covita.net | 800.707.5751 | info@covita.net



Visit www.bedfont.com/resources to view this document in other languages.



Bedfont Scientific Ltd. Station Road, Harrietsham, Maidstone nt, ME17 1JA, England. Tel: +44 (0)1622 851122, Fax: +44 (0)1622 854860 Email: ask@bedfont.com Web: www.bedfont.com

Cristimar F4-1 Ave Juan Carlos I Los Cristianos, Arona, 38650 nta Cruz de Tenerife. Spain





© Bedfont* Scientific Limited 221

Issue 3- October 2021, Part No: LAB742 AX Bedfont® Scientific Limited reserve the right to change or update this literature without prior notice Registered in: England and Wales. Registered No: 1289798